















Vessel Info

Full specification overleaf

Seven Oceanic is a deepwater subsea operations vessel.

- Length 156.9m x breadth 27.0m
- Deck area 2,300m²
- Heave compensated 400t crane
- DP III class
- 1x 3,000t underdeck carousel

- DNV clean design results in low fuel consumption
- Accommodation for 140 people
- Maximum speed 17.6 knots

Fast Facts

- Optimised sea-keeping hull for fast transit speed and low fuel consumption
- Ice class C rating which allows for operations in both the Barents and Northern North Sea
- · AHC available on both port and starboard sides, and through moon pool area

General Information	
Type Classification Year Built	Construction / Flex-lay DNV 1A1, ICE C, SF, COMF-V(3), C(3), HELD-SH, CRANE E0, DYNPOS-AUTRO, NAUT-AW, CLEAN DESIGN VIBR DK(+), TMON 2011
Principal Dimensions	
Length Overall Breadth Gross Tonnage	156.9m 27.0m 16,511t
Power and Propulsion	
Maximum Speed Economical Speed	17.6 knots 12.0 knots
Propulsion	
Main Engines Emergency Generator	2x Wartsila W8L32 each with a capacity of 3,840kW 2x Wartsila W12V32 each with a capacity of 5,760kW 1x CAT 3512 producing 1,360kW
Propulsion	/ 300kW in harbour or emergency modes respectively 2x Tunnel thrusters RR Ulstein TT2,650 DPB CP, max power for each unit 1,900kW 2x Retractable azimuth thrusters RR Aquamaster UL2001 FP, max power of each unit 1,500kW 2x Propulsion azimuth thrusters RR Aquamaster Contaz 25, max power of each unit 3,000kW 1x Shaft line propeller, RR Ulstein
	86XF5 – 3,700, max motor power 4,000kW
Tank Capacities (100%)	
Fuel Oil (approx)	2,199.3m³

8,864.1m³

1,641.9m³

Ballast Water (approx)

Fresh Water (approx)

DNV DYNPOS AUTRO 3 (DP III) Kongsberg K-POS DP 21
Kongsberg K-POS DP 21
400t at 15m
400t at 15m
3,000m 20t single/40t double 2,600m single/1,300m double 100t at 15m 2,000m 10t
2x 3t at 15m 4x 12t Constant Tension
One underdeck basket carousel 3,000t 23.6m 5.6m 2,336m³ Capacity for 4x 360t deck reels
1 7.2 x 7.2m
2x Hercules 3,000m

Accommodation	
Berths Single cabins Double cabins	140 58 41
Mess Room/Rec Room	1/4
Helideck	
Туре	Marine aluminum for BSL D5-1, HCA
Diameter	20.9m
Ice and Winterisation	

Features include hull plate strengthening. Trace heating of helideck, lifeboat, and other critical areas. Tank heating of fresh water tanks, and other measures.





client.enquiry@subsea7.com



www.subsea7.com

















